Material Name: Super Sap CCF Hardener

* * * Section 1 - Product and Company Identification * * *

Manufacturer Information

Entropy Resins, Inc. 30621 San Antonio St. Hayward, CA 94544 USA Phone: +1-310-882-2582

Emergency # +1-760-476-3962 Global Response Contract:

333178

Hijos De A. Ferrer-Dalmau C/ Rosalia de Castro 21 08025 Barcelona Spain

* * * Section 2 - Hazards Identification * * *

GHS Classification:

Skin Corrosion - Category 1B Serious Eye Damage - Category 1 Skin Sensitization - Category 1 Reproductive Toxicity - Category 2

GHS LABEL ELEMENTS Symbol(s)



Signal Word

Danger

Hazard Statements

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility.

Precautionary Statements

Prevention

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective glove/protective/clothing/eye protection/face protection.

Contaminated work clothing should not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Material Name: Super Sap CCF Hardener

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/attention.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

* * * Section 3 - Composition / Information on Ingredients * * *

CAS#	Component	Percent
9046-10-0	Propylene glycol diamine, 2-amino-, diether with Propylene	10-80
102-71-6	Triethanolamine	<10
110-85-0	Piperazine	<8
140-31-8	1-(2-Aminoethyl) piperazine	<5

* * * Section 4 - First Aid Measures * * *

First Aid: Eyes

For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. If physician is not available, flush for an additional 15 minutes. Seek immediate medical attention.

First Aid: Skin

For skin contact, under a safety shower, immediately remove contaminated clothing and shoes. Wash affected areas thoroughly with large amounts of water, and soap if available, for at least 15 minutes. Seek immediate medical attention. Discard or decontaminate clothing before re-use and destroy contaminated shoes.

First Aid: Ingestion

If swallowed, immediately give at least 3-4 glasses of water, but do not induce vomiting. If vomiting occurs, give fluids again. Do not give anything by mouth to an unconscious or convulsing person. Seek immediate medical attention.

First Aid: Inhalation

Remove to fresh air.

** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

Not classified as flammable, but will burn.

Hazardous Combustion Products

Carbon monoxide may be involved incomplete combustion occurs.

Page 2 of 9	Issue Date 05/08/12 Revision 1.0000	Print Date: 6/15/2012

Material Name: Super Sap CCF Hardener

Extinguishing Media

Dry chemical powder, carbon dioxide, foam, water spray or fog, sand or earth.

Unsuitable Extinguishing Media

None

Fire Fighting Equipment/Instructions

Firefighters should wear full protective clothing and self-contained breathing apparatus. Keep adjacent containers cool by spraying with water.

* * * Section 6 - Accidental Release Measures * * *

Recovery and Neutralization

Stop the flow of material, if this is without risk.

Materials and Methods for Clean-Up

Absorb or contain liquid with sand, earth or other absorbent spill control material. Shovel material to labeled sealable container for safe disposal. Do not use sawdust, wood chips or other cellulosic materials to absorb the spill, as the possibility for spontaneous combustion exists. Wash spill residue with warm, soapy water if necessary.

Emergency Measures

Isolate area. Keep unnecessary personnel away.

Personal Precautions and Protective Equipment

Wear protective clothing specified for normal operations.

Environmental Precautions

Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. If material enters drains it should be pumped out into an open vessel. Emergency services may need to be called to assist in this operation.

Prevention of Secondary Hazards

None

* * * Section 7 - Handling and Storage * * *

Handling Procedures

Avoid contact with skin, eyes and clothing

Storage Procedures

Keep container tightly closed and dry. Palletized loads should be stacked to a maximum of 4 high. Protect from heat, moisture and direct sunlight.

Incompatibilities

Monomers, resins, water and oxidising agents.

Material Name: Super Sap CCF Hardener

* * * Section 8 - Exposure Controls / Personal Protection * * *

Component Exposure Limits

Triethanolamine (203-049-8)

ACGIH: 5 mg/m3 TWA

Austria: 1.6 ppm STEL [KZW] (4 X 15 min); 10 mg/m3 STEL [KZW] (inhalable fraction, 4 X 15 min)

0.8 ppm TWA [TMW]; 5 mg/m3 TWA [TMW] (inhalable fraction)

Sensitizer

Belgium: 5 mg/m3 TWA

Denmark: 0.5 ppm TWA; 3.1 mg/m3 TWA

Finland: 5 mg/m3 TWA

Germany: 5 mg/m3 TWA MAK (inhalable fraction)

20 mg/m3 Peak

Ireland: 5 mg/m3 TWA

Portugal: 5 mg/m3 TWA [VLE-MP] Spain: 5 mg/m3 TWA [VLA-ED]

Sweden: 5 mg/m3 LLV

10 mg/m3 STV

Piperazine (203-808-3)

ACGIH: 0.03 ppm TWA (inhalable fraction and vapor)

Sensitizer

Austria: 0.3 mg/m3 STEL [KZW] (4 X 15 min)

0.1 mg/m3 TWA [TMW] (reaction with nitrosating agents can lead to formation of carcinogens N-

N'-Dinitrosopiperazine)

Belgium: 0.3 mg/m3 STEL

0.1 mg/m3 TWA

Denmark: 0.003 ppm TWA; 0.1 mg/m3 TWA Finland: 0.084 ppm STEL; 0.3 mg/m3 STEL

0.028 ppm TWA; 0.1 mg/m3 TWA

France: 0.3 mg/m3 STEL [VLCT] (indicative limit, powder and vapor)

0.1 mg/m3 TWA [VME] (indicative limit, dust and vapor)

Germany: 0.1 mg/m3 TWA AGW (exposure factor 1)

Greece: 0.3 mg/m3 STEL (dust or vapor)

0.1 mg/m3 TWA (dust or vapor)

Ireland: 0.3 mg/m3 STEL

0.1 mg/m3 TWA

Sensitizer

Italy: 0.1 mg/m3 TWA (dust and vapor)

Netherlands: 0.3 mg/m3 STEL

0.1 mg/m3 TWA

Spain: 0.3 mg/m3 STEL [VLA-EC]

0.1 mg/m3 TWA [VLA-ED] (indicative limit value; reaction with Nitrosating agents can lead to

formation of carcinogenic N-Nitrosamines)

sensitizer

Sweden: 0.1 ppm LLV; 0.3 mg/m3 LLV

0.3 ppm STV; 1 mg/m3 STV

Engineering Measures

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Material Name: Super Sap CCF Hardener

Personal Protective Equipment: Respiratory

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: Hands

Wear impervious nitride rubber gloves or butyl rubber gloves, gauntlet type.

Personal Protective Equipment: Eyes

Monogoggles.

Personal Protective Equipment: Skin and Body

Standard issue work clothes, safety boots.

Section 9 - Physical & Chemical Properties

Appearance: Clear to yellow Odor: Ammoniacal

Physical State: Liquid pH: ND Vapor Density: ND Vapor Pressure: ND Melting Point: ND Boiling Point: ND

Specific Gravity: 920 - 1000 kg/m3 @ 25 C (Solubility (H2O): Negligible

typical)

Evaporation Rate: ND VOC: ND Viscosity: 0.05 - 0.2 Pa.s @ 25 C Octanol/H2O Coeff.: ND

Flash Point: ND Flash Point Method: ND Upper Flammability Limit ND Lower Flammability Limit ND (UFL):

(LFL):

Burning Rate: ND Auto Ignition: >100°C

* * * Section 10 - Chemical Stability & Reactivity Information

Chemical Stability

Stable under normal use conditions.

Hazardous Reaction Potential

Will not occur.

Conditions to Avoid

None

Incompatible Products

Reacts with monomers, resins and strong oxidising agents.

Hazardous Decomposition Products

Hazardous decomposition products are not expected to form during normal storage.

Section 11 - Toxicological Information

Acute Toxicity

Component Analysis - LD50/LC50

Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)

Oral LD50 Rat 242 mg/kg; Dermal LD50 Rabbit 360 mg/kg

Triethanolamine (102-71-6)

Oral LD50 Rat 4190 mg/kg; Dermal LD50 Rabbit >2000 mg/kg; Dermal LD50 Rat >16 mL/kg

Page 5 of 9 Issue Date 05/08/12 Revision 1.0000 Print Date: 6/15/2012

Material Name: Super Sap CCF Hardener

Piperazine (110-85-0)

Oral LD50 Rat 1900 mg/kg; Dermal LD50 Rabbit 4000 mg/kg

1-(2-Aminoethyl) piperazine (140-31-8)

Oral LD50 Rat 2140 mg/kg; Dermal LD50 Rabbit 880 mg/kg

Potential Health Effects: Skin Corrosion Property/Stimulativeness

Causes severe skin burns.

Potential Health Effects: Eye Critical Damage/ Stimulativeness

Causes eye damage.

Potential Health Effects: Ingestion

Harmful if swallowed.

Potential Health Effects: Inhalation

Causes severe irritation if inhaled.

Respiratory Organs Sensitization/Skin Sensitization

May cause an allergic skin and respiratory reaction.

Generative Cell Mutagenicity

This product is not reported to have any mutagenic effects.

Carcinogenicity

A: General Product Information

This product is not reported to have any carcinogenic effects.

B: Component Carcinogenicity

Triethanolamine (102-71-6)

IARC: Monograph 77 [2000] (Group 3 (not classifiable))

Piperazine (110-85-0)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

Reproductive Toxicity

Suspected of damaging fertility.

Specified Target Organ General Toxicity: Single Exposure

This product is not reported to have any single exposure specific target organ toxicity effects.

Specified Target Organ General Toxicity: Repeated Exposure

This product is not reported to have any repeat exposure specific target organ toxicity effects.

Aspiration Respiratory Organs Hazard

This product is not reported to have any aspiration hazard effects.

* * * Section 12 - Ecological Information * * *

Ecotoxicity

A: General Product Information

This product is not reported to have any ecotoxicity effects.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Triethanolamine (102-71-6)

Test & Species Conditions

Material Name: Super Sap CCF Hardener

96 Hr LC50 Pimephales promelas 10600-13000 mg/L

[flow-through]

96 Hr LC50 Pimephales promelas >1000 mg/L [static] 96 Hr LC50 Lepomis macrochirus 450-1000 mg/L

[static]

72 Hr EC50 Desmodesmus 216 mg/L

subspicatus

96 Hr EC50 Desmodesmus 169 mg/L

subspicatus

24 Hr EC50 Daphnia magna 1386 mg/L

Piperazine (110-85-0)

Test & Species Conditions

96 Hr LC50 Lepomis macrochirus >10000 mg/L [static]

96 Hr EC50 water flea 6915 mg/L

1-(2-Aminoethyl) piperazine (140-31-8)

Test & Species Conditions

96 Hr LC50 Pimephales promelas 1950-2460 mg/L

[flow-through]

96 Hr LC50 Poecilia reticulata >1000 mg/L [semi-

static]

96 Hr LC50 Oncorhynchus mykiss >=100 mg/L [semi-

static]

72 Hr EC50 Pseudokirchneriella

495 mg/L

subcapitata

48 Hr EC50 Daphnia magna 32 mg/L

Persistence/Degradability

No information available for the product.

Bioaccumulation

No information available for the product.

Mobility in Soil

No information available for the product.

* * * Section 13 - Disposal Considerations * * *

Waste Disposal Instructions

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

Disposal of Contaminated Containers or Packaging

Dispose of contents/container in accordance with local/regional/national/international regulations.

* * * Section 14 - Transportation Information * * *

IATA Information

Shipping Name: Polyamines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine)

UN #: 2735 Hazard Class: 8 Packing Group: III

Material Name: Super Sap CCF Hardener

ICAO Information

Shipping Name: Polyamines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine)

UN #: 2735 Hazard Class: 8 Packing Group: III

IMDG Information

Shipping Name: Polyamines, liquid, corrosive, n.o.s. (Polyoxypropylenediamine)

UN #: 2735 Hazard Class: 8 Packing Group: III

* * * Section 15 - Regulatory Information * * *

Regulatory Information

EU MARKING AND LABELLING:

Symbol(s):

C

Risk Phrases:

R34 Causes burns.

R42/43 May cause sensitization by inhalation and skin contact.

R62 Possible risk of impaired fertility.

R63 Possible risk of harm to the unborn child.

Substance Analysis - Inventory

Component/CAS	EC#	EEC	CAN	TSCA
Propylene glycol diamine, 2-amino-, diether with	618-561-0	No	DSL	Yes
Propylene				
9046-10-0				
Triethanolamine	203-049-8	EINECS	DSL	Yes
102-71-6				
Piperazine	203-808-3	EINECS	DSL	Yes
110-85-0				
1-(2-Aminoethyl) piperazine	205-411-0	EINECS	DSL	Yes
140-31-8				

* * * Section 16 - Other Information * * *

Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; ADG = Australian Code for the Transport of Dangerous Goods by Road and Rail; ADR/RID = European Agreement of Dangerous Goods by Road/Rail; AS = Standards Australia; DFG = Deutsche Forschungsgemeinschaft; DOT = Department of Transportation; DSL = Domestic Substances List; EEC = European Economic Community; EINECS = European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EU = European Union; HMIS = Hazardous Materials Identification System; IARC = International Agency for Research on Cancer; IMO = International Maritime Organization; IATA = International Air Transport Association; MAK = Maximum Concentration Value in the Workplace; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Association; NOHSC = National Occupational Health & Safety Commission; NTP = National Toxicology Program; STEL = Short-term Exposure Limit; TDG = Transportation of Dangerous Goods; TLV = Threshold Limit Value; TSCA = Toxic Substances Control Act; TWA = Time Weighted Average

Material Name: Super Sap CCF Hardener

Literature References

None

Other Information

USER'S RESPONSIBILITY / DISCLAIMER OF LIABILITY: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as a guarantee of any specific property of the product.

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

This bulletin cannot cover all possible situations that the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to develop appropriate work practice guidelines and employee instructional programs for your operation.

End of Sheet